



BRILL® Mixed Viscosity Table

0W-20 × 20W-60

0W-20	20W-60	Viscosity(40°C)	Viscosity(100°C)	Mixed Viscosity Grade
100%	0%	43.2	8.15	0W-20
95%	5%	46.4	8.59	2.5W-25
90%	10%	49.7	9.06	5W-25
85%	15%	53.4	9.55	5W-30
80%	20%	57.3	10.1	5W-30
75%	25%	61.5	10.6	7.5W-30
70%	30%	66.1	11.2	7.5W-35
65%	35%	71.0	11.8	7.5W-35
60%	40%	76.3	12.5	10W-35
55%	45%	82.0	13.2	10W-40
50%	50%	88.1	13.9	12.5W-40
45%	55%	94.7	14.7	12.5W-40
40%	60%	101.7	15.5	15W-45
35%	65%	109.4	16.4	15W-45
30%	70%	117.6	17.4	17.5W-50
25%	75%	126.5	18.4	17.5W-50
20%	80%	136.0	19.4	17.5W-55
15%	85%	146.3	20.5	20W-55
10%	90%	157.3	21.7	20W-55
5%	95%	169.3	22.9	20W-60
0%	100%	182.1	24.3	20W-60

Unit for Viscosity mm²/S